

# An Augmented Lagrangian Filter Method\*

Sven Leyffer<sup>†</sup>

Charlie Vanaret<sup>‡</sup>

July 29, 2019

## Abstract

**Changes to previous version are marked in red.**

We introduce a filter mechanism to enforce convergence for augmented Lagrangian methods for nonlinear programming. In contrast to traditional augmented Lagrangian methods, our approach does not require the use of forcing sequences that drive the first-order error to zero. Instead, we employ a filter to drive the optimality measures to zero. Our algorithm is flexible in the sense that it allows for equality-constrained quadratic programming steps to accelerate local convergence. We also include a feasibility restoration phase that allows fast detection of infeasible problems. We provide a convergence proof that shows that our algorithm converges to first-order stationary points. **We provide preliminary numerical results that demonstrate the effectiveness of our proposed method.**

R.Ed

**Keywords:** Augmented Lagrangian, filter methods, nonlinear optimization.

AMS-MSC2000: 90C30

## 1 Introduction

Nonlinearly constrained optimization is one of the most fundamental problems in scientific computing with a broad range of engineering, scientific, and operational applications. Examples include nonlinear power flow [4, 31, 57, 61, 65], gas transmission networks [33, 56, 16], the coordination of hydroelectric energy [23, 18, 63], and finance [28], including portfolio allocation [51, 43, 72] and volatility estimation [25, 2]. Chemical engineering has traditionally been at the forefront of developing new applications and algorithms for nonlinear optimization; see the surveys [11, 12]. Applications in chemical engineering include process flowsheet design, mixing, blending, and equilibrium models. Another area with a rich set of applications is optimal control [10]; optimal control applications include the control of chemical reactions, the shuttle re-entry problem [17, 10], and the control of multiple airplanes [3]. More importantly, nonlinear optimization is a basic building block of more complex design and optimization paradigms, such as **mixed-integer nonlinear optimization** [1, 34, 48, 52, 14, 5] and optimization problems with complementarity constraints [53, 64, 54].

R.1

---

\*Preprint ANL/MCS-P6082-1116

<sup>†</sup>Mathematics and Computer Science Division, Argonne National Laboratory, Lemont, IL 60439, USA, [leyffer@mcs.anl.gov](mailto:leyffer@mcs.anl.gov).

<sup>‡</sup>Fraunhofer ITWM, Fraunhofer-Platz 1, 67663 Kaiserslautern, Germany, [charlie.vanaret@itwm.fraunhofer.de](mailto:charlie.vanaret@itwm.fraunhofer.de)

Nonlinearly constrained optimization has been studied intensely for more than 30 years, resulting in a wide range of algorithms, theory, and implementations. Current methods fall into two competing classes, both Newton-like schemes: active-set methods [44, 45, 35, 19, 24, 39] and interior-point methods [40, 50, 70, 69, 8, 68, 20, 21]. While both have their relative merits, interior-point methods have emerged as the computational leader for large-scale problems.

The Achilles' heel of interior-point methods is the lack of efficient warm-start strategies. Despite significant recent advances [46, 6, 7], interior-point methods cannot compete with active-set approaches when solving mixed-integer nonlinear programs [15]. This deficiency is at odds with the rise of complex optimization paradigms, such as nonlinear integer optimization that require the solution of thousands of closely related nonlinear problems and drive the demand for efficient warm-start techniques. On the other hand, active-set methods exhibit an excellent warm-starting potential. Unfortunately, current active-set methods rely on pivoting approaches and do not readily scale to multicore architectures (though some successful parallel approaches to linear programming (LP) active-set solvers can be found in the series of papers [49, 67, 55]). To overcome this challenge, we study augmented Lagrangian methods, which combine better parallel scalability potential with good warm-starting capabilities.

R.1

We consider solving the following nonlinear program (NLP):

$$\begin{aligned} & \underset{x}{\text{minimize}} && f(x) \\ & \text{subject to} && c(x) = 0 \\ & && l \leq x \leq u \end{aligned} \tag{NLP}$$

where  $x \in \mathbb{R}^n$ ,  $f : \mathbb{R}^n \rightarrow \mathbb{R}$ ,  $c : \mathbb{R}^n \rightarrow \mathbb{R}^m$  are twice continuously differentiable. We use superscripts  $\cdot^{(k)}$  to indicate iterates, such as  $x^{(k)}$ , and evaluation of nonlinear functions, such as  $f^{(k)} := f(x^{(k)})$  and  $\nabla c^{(k)} = \nabla c(x^{(k)})$ . The Lagrangian of (NLP) is defined as

$$\mathcal{L}(x, y) = f(x) - y^T c(x), \tag{1.1}$$

where  $y \in \mathbb{R}^m$  is a vector of Lagrange multipliers of  $c(x) = 0$ .

The first-order optimality conditions of (NLP) can be written as

$$\min \{x - l, \max \{x - u, \nabla_x \mathcal{L}(x, y)\}\} = 0 \tag{1.2a}$$

$$c(x) = 0, \tag{1.2b}$$

where the min and max are taken componentwise. It can be shown that (1.2a) is equivalent to the standard Karush-Kuhn-Tucker (KKT) conditions for (NLP). Introducing Lagrange multipliers  $z$  for the simple bounds, the KKT conditions are

$$\nabla \mathcal{L}(x, y) - z = 0, \quad c(x) = 0, \quad l \leq x \leq u \perp z$$

where  $\perp$  represents complementarity, and means that  $z_i = 0$  if  $l_i < x_i < u_i$ , and that  $z_i \geq 0$  and  $z_i \leq 0$  if  $x_i = l_i$  and  $x_i = u_i$ , respectively. This complementarity condition is equivalent to  $\min\{x - l, \max\{x - u, z\}\} = 0$ , and hence the KKT conditions are equivalent to (1.2a).

## 1.1 Augmented Lagrangian Methods

The augmented Lagrangian is defined as

$$\begin{aligned} \mathcal{L}_\rho(x, y) &= f(x) - y^T c(x) + \frac{1}{2} \rho \|c(x)\|^2 \\ &= \mathcal{L}_0(x, y) + \frac{1}{2} \rho \|c(x)\|^2, \end{aligned} \tag{1.3}$$

for a given penalty parameter  $\rho$ . The Lagrangian (1.1) is therefore given by  $\mathcal{L}_0(x, y)$ , that is (1.3) with  $\rho = 0$ . Augmented Lagrangian methods have been studied by [9, 62, 60]. Recently, researchers have expressed renewed interest in augmented Lagrangian methods because of their good scalability properties, which had already been observed in [26]. The key computational step in **bound-constrained** augmented Lagrangian methods, **such as LANCELOT**, [26], is the minimization of  $x \mapsto \mathcal{L}_{\rho_k}(x, y^{(k)})$  for given  $\rho_k > 0$  and  $y^{(k)} \in \mathbb{R}^m$ , giving rise to the bound-constrained Lagrangian (**BCL**( $y^{(k)}, \rho_k$ )) problem: R.2.2

$$\begin{aligned} & \underset{x}{\text{minimize}} && \mathcal{L}_{\rho_k}(x, y^{(k)}) \\ & \text{subject to} && l \leq x \leq u. \end{aligned} \quad (\text{BCL}(y^{(k)}, \rho_k))$$

We denote the solution of (**BCL**( $y^{(k)}, \rho_k$ )) by  $x^{(k+1)}$ . A basic augmented Lagrangian method solves (**BCL**( $y^{(k)}, \rho_k$ )) approximately and updates the multipliers using the so-called first-order multiplier update: R.2.3

$$y^{(k+1)} = y^{(k)} - \rho_k c(x^{(k+1)}). \quad (1.4)$$

Traditionally, augmented Lagrangian methods have used two forcing sequences,  $\eta_k \searrow 0$  and  $\omega_k \searrow 0$ , to control the infeasibility and first-order error, and enforce global convergence. Sophisticated update schemes for  $\eta, \omega$  can be found in [27]. **Motivated by the KKT conditions (1.2a), we define the primal and dual infeasibility as**

$$\eta(x) := \|c(x)\|. \quad (1.5a)$$

$$\omega_\rho(x, y) := \|\min\{x - l, \max\{x - u, \nabla_x \mathcal{L}_\rho(x, y)\}\}\| \quad (1.5b)$$

and observe that  $\omega_0(x, y)$  is the dual feasibility error of (**NLP**). Moreover, the first-order multiplier update implies that

$$\nabla_x \mathcal{L}_0(x^{(k+1)}, y^{(k+1)}) = \nabla f(x^{(k+1)}) - \nabla c(x^{(k+1)})^T y^{(k)} + \rho_k \nabla c(x^{(k+1)})^T c(x^{(k+1)}) = \nabla \mathcal{L}_{\rho_k}(x^{(k+1)}, y^{(k)}).$$

Hence, it follows that

$$\omega_0(x^{(k+1)}, y^{(k+1)}) = \omega_{\rho_k}(x^{(k+1)}, y^{(k)}),$$

which is the dual feasibility error of (**BCL**( $y^{(k)}, \rho_k$ )). Hence, we can monitor the dual infeasibility error of (**NLP**) whilst solving (**BCL**( $y^{(k)}, \rho_k$ )).

A rough outline of an augmented Lagrangian method is given in Algorithm 1; we use a double-loop representation to simplify the comparison to our proposed filter method.

Given sequences  $\eta_k \searrow 0$  and  $\omega_k \searrow 0$ , an initial point  $(x^{(0)}, y^{(0)})$  and  $\rho_0$ , set  $k \leftarrow 0$

**while**  $(x^{(k)}, y^{(k)})$  not optimal **do**

  Set  $j \leftarrow 0$  and initialize  $\hat{x}^{(j)} \leftarrow x^{(k)}$

  Set up the augmented Lagrangian subproblem (**BCL**( $y^{(k)}, \rho_k$ ))

**while**  $\omega_{\rho_k}(\hat{x}^{(j)}, y^{(k)}) > \omega_k$  and  $\eta(\hat{x}^{(j)}) > \eta_k$  (not acceptable) **do**

$\hat{x}^{(j+1)} \leftarrow$  approximate argmin  $\mathcal{L}_{\rho_k}(x, y^{(k)})$  from initial point  $\hat{x}^{(j)}$

**if**  $\omega_{\rho_k}(\hat{x}^{(j)}, y^{(k)}) \leq \omega_k$  but  $\eta(\hat{x}^{(j)}) > \eta_k$  **then**

      | Increase penalty parameter  $\rho_k \leftarrow 2\rho_k$

**else**

      | Update multipliers:  $\hat{y}^{(j+1)} \leftarrow y^{(k)} - \rho_k c(\hat{x}^{(j+1)})$

    Set  $j \leftarrow j + 1$

  Set  $(x^{(k+1)}, y^{(k+1)}) \leftarrow (\hat{x}^{(j)}, \hat{y}^{(j)})$ , update  $\rho_{k+1} \leftarrow \rho_k$ , and increase  $k \leftarrow k + 1$

**Algorithm 1: Classical Bound-Constrained Augmented Lagrangian Method.**

Our goal is to improve traditional augmented Lagrangian methods in three ways, extending the augmented Lagrangian filter methods developed in [42] for quadratic programs to general NLPs:

1. Replace the forcing sequences  $(\eta_k, \omega_k)$  by a less restrictive algorithmic construct, namely a filter (defined in Section 2);
2. Introduce a second-order step to promote fast local convergence, similar to recent sequential linear quadratic programming (SLQP) methods [19, 24, 39];
3. Equip the augmented Lagrangian method with a fast and robust detection of infeasible subproblems [37].

In [13], the authors study a related approach in which the augmented Lagrangian algorithm is used to find an approximate minimizer (e.g. to a tolerance of  $10^{-4}$ ), and then a crossover is performed to an interior-point method or a Newton method on the active constraints. In contrast, we propose a method that more naturally integrates second-order steps within the augmented Lagrangian framework.

This paper is organized as follows. The next section defines the filter for augmented Lagrangians, and outlines our method. Section 3 presents the detailed algorithm and its components, and Section 4 presents the global convergence proof. **In Section 5, we present some promising numerical results.** We close the paper with some conclusions and outlooks.

R.Ed

## 2 An Augmented Lagrangian Filter

This section defines the basic concepts of our augmented Lagrangian filter algorithm. We start by defining a suitable filter and related step acceptance conditions. We then provide an outline of the algorithm that is described in more detail in the next section.

The new augmented Lagrangian filter is defined by using the residual of the first-order conditions (1.2a), defined in (1.5). Augmented Lagrangian methods use forcing sequences  $(\omega_k, \eta_k)$  to drive  $\omega_0(x, y)$  and  $\eta(x)$  to zero. Here, we instead use the filter mechanism [38, 36] to achieve convergence to first-order points. A filter is formally defined as follows.

R.1

**Definition 2.1** (Augmented Lagrangian Filter and Acceptance). *A filter  $\mathcal{F}$  is a list of pairs  $(\eta_l, \omega_l) := (\eta(x^{(l)}), \omega_0(x^{(l)}, y^{(l)}))$  such that no pair dominates another pair, i.e. there exists no pairs  $(\eta_l, \omega_l), (\eta_k, \omega_k), l \neq k$  such that  $\eta_l \leq \eta_k$  and  $\omega_l \leq \omega_k$ . A point  $(x^{(k)}, y^{(k)})$  is acceptable to the filter  $\mathcal{F}$  if and only if*

$$\eta_k := \eta(x^{(k)}) \leq \beta\eta_l \quad \text{or} \quad \omega_k := \omega_0(x^{(k)}, y^{(k)}) \leq \omega_l - \gamma\eta(x^{(k)}), \quad \forall (\eta_l, \omega_l) \in \mathcal{F}. \quad (2.6)$$

where  $0 < \gamma, \beta < 1$  are constants.

**In our algorithm, we maintain a filter,  $\mathcal{F}_k$ , at iteration  $k$ , with the property that  $\eta_l > 0$  for all  $l \in \mathcal{F}_k$ .** The fact that  $(\eta(x), \omega_0(x, y)) \geq 0$  implies that we have an automatic upper bound on  $\eta(x)$  for all points that are acceptable:

R.2.4

$$\eta(x) \leq U := \max(\omega_{\min}/\gamma, \beta\eta_{\min}), \quad (2.7)$$

where  $\omega_{\min}$  is the smallest first-order error of any filter entry, that is  $\omega_{\min} := \min\{\omega_l : (\eta_l, \omega_l) \in \mathcal{F}\}$ , and the smallest infeasibility is  $\eta_{\min} := \min\{\eta_l : (\eta_l, \omega_l) \in \mathcal{F} \text{ and } \eta_l > 0\}$ , see Figure 1. The point  $(\eta_{\min}, \omega_{\min})$  is the ideal filter entry.




Figure 1: Example of an augmented Lagrangian filter  $\mathcal{F}$  with three entries. The filter is in blue, the dashed green line shows the envelope in  $\eta$ , and the upper bound  $U$  (red line) is implied by the sloping envelope condition (2.6) and  $\omega_0 \geq 0$ . Values above and to the right of the filter are not acceptable. The green area shows the set of filter entries that are guaranteed to be acceptable, and the shaded purple area is the set of entries that trigger the switch to restoration.

We note that our filter is based on the Lagrangian and not on the augmented Lagrangian. This choice is deliberate: one can show that the gradient of the Lagrangian after the first-order multiplier update (1.4) equals the gradient of the augmented Lagrangian, namely:

$$\nabla_x \mathcal{L}_0(x^{(k)}, y^{(k)}) = \nabla_x \mathcal{L}_{\rho_k}(x^{(k)}, y^{(k-1)}). \quad (2.8)$$

Thus, by using the Lagrangian, we ensure that filter-acceptable points remain acceptable after the first-order multiplier update. Moreover, (2.8) shows that the filter acceptance can be readily checked during the minimization of the augmented Lagrangian, in which the multiplier is fixed and we iterate over  $x$  only.

The filter envelope defined by  $\beta$  and  $\gamma$  ensures that iterates cannot accumulate at points where  $\eta > 0$ , and it promotes convergence (see Lemma 4.4). A benefit of the filter approach is that we do not need to assume that the multipliers remain bounded or that the iterates remain in a compact set, although we assume later that there exists no feasible points at infinity. We outline the main algorithmic ideas in Algorithm 2; in the next section we provide a detailed description of the algorithm and its main components.

Algorithm 2 has an inner iteration in which we minimize the augmented Lagrangian until a filter-acceptable point is found. Inner iterates are distinguished by a “hat”, that is  $\hat{x}^{(j)}$ . Outer iterates are denoted by  $x^{(k)}$ . A restoration phase is invoked if the iterates fail to make progress toward feasibility. The outline of our algorithm is deliberately vague to convey the main ideas. Details of the conditions of switching to restoration, termination of the inner iteration, and increase of the penalty parameter are developed in the next section. The algorithm supports an optional penalty increase condition, which triggers a heuristic to estimate the penalty parameter. In addition, our algorithm implements an optional second-order step on the set of active constraints. Our analysis, however, concentrates on the plain augmented Lagrangian approach.

We note, that most of the effort of Algorithm 2 is in the solution of the approximate minimization of the augmented Lagrangian, for which efficient methods exist, such as bound-constrained

R.1

```

Given  $(x^{(0)}, y^{(0)})$  and  $\rho_0$ , set  $\omega_0 \leftarrow \omega(x^{(0)}, y^{(0)})$ ,  $\eta_0 \leftarrow \eta(x^{(0)})$ ,  $\mathcal{F}_0 \leftarrow \{(\eta_0, \omega_0)\}$ , and  $k \leftarrow 0$ 
while  $(x^{(k)}, y^{(k)})$  not optimal do
  Set  $j \leftarrow 0$ , and initialize  $\hat{x}^{(j)} \leftarrow x^{(k)}$ 
  while  $(\hat{\eta}_j, \hat{\omega}_j)$  not acceptable to  $\mathcal{F}_k$  do
     $\hat{x}^{(j+1)} \leftarrow \underset{l \leq x \leq u}{\text{approximate argmin}} \mathcal{L}_{\rho_k}(x, y^{(k)})$  from initial point  $\hat{x}^{(j)}$ 
    if restoration switching condition holds then
      Increase penalty:  $\rho_{k+1} \leftarrow 2\rho_k$ 
      Switch to restoration to find acceptable  $(\hat{\eta}_j, \hat{\omega}_j)$ 
    Update multipliers:  $\hat{y}^{(j+1)} \leftarrow \hat{y}^{(j)} - \rho_k c(\hat{x}^{(j+1)})$ 
    Set  $j \leftarrow j + 1$ 
  Set  $(x^{(k+1)}, y^{(k+1)}) \leftarrow (\hat{x}^{(j)}, \hat{y}^{(j)})$ 
  if  $\eta_{k+1} > 0$  then
    Add  $(\eta_{k+1}, \omega_{k+1})$  to  $\mathcal{F}_k$  (only points with  $\eta_{k+1} > 0$  are added)
  Set  $k \leftarrow k + 1$ 

```

**Algorithm 2:** Outline of Augmented Lagrangian Filter Method

projected-gradient conjugate-gradient methods, see, e.g. [58, 22]

R.2.6

### 3 Detailed Algorithm Statement

We start by describing the four algorithmic components not presented in our outline: the penalty update, the restoration switching condition, the termination condition for the inner iteration, and the second-order step. We then discuss the complete algorithm.

#### 3.1 Optional Penalty Update Heuristic

Augmented Lagrangian methods can be shown to converge provided that the penalty parameter is sufficiently large and the multiplier estimate is sufficiently close to the optimal multiplier; see, for example, [9]. Here, we extend the penalty estimate from [42] to nonlinear functions. We stress that this step of the algorithm is not needed for global convergence, although it has been shown that these steps improve the behavior of our method in the context of QPs [42]. We will show in Section 4 that the penalty update is bounded, so that our heuristic does not harm the algorithm.

Consider the Hessian of the augmented Lagrangian,  $\mathcal{L}_\rho(x, y)$ :

R.1

$$\nabla^2 \mathcal{L}_\rho = \nabla^2 \mathcal{L}_0 + \rho \nabla c \nabla c^T + \rho \sum_{i=1}^m c_i \nabla^2 c_i, \quad (3.9)$$

which includes the usual Lagrangian Hessian,  $\nabla^2 \mathcal{L}_0(x, y)$ , and the last two terms that represent the Hessian of the penalty term,  $\frac{\rho}{2} \|c(x)\|_2^2$ . Ideally, we would want to ensure  $\nabla^2 \mathcal{L}_\rho \succeq 0$  at the solution. Instead, we drop the  $\nabla^2 c_i$  terms and consider

R.2.7

$$\nabla^2 \mathcal{L}_\rho \approx \nabla^2 \mathcal{L}_0 + \rho \nabla c \nabla c^T. \quad (3.10)$$

Now, we use the same ideas as in [42] to develop a penalty estimate that ensures that the augmented Lagrangian is positive definite on the null space of the active inequality constraints. We

define the active set and the inactive set as

$$\mathcal{A}^k := \mathcal{A}(x^{(k)}) := \left\{ i : x_i^{(k)} = l_i \text{ or } x_i^{(k)} = u_i \right\} \quad \text{and} \quad \mathcal{I}^k := \{1, 2, \dots, n\} - \mathcal{A}^k, \quad (3.11)$$

respectively.

Next, we define reduced Hessian and Jacobian matrices. For a set of row and column indices  $\mathcal{R}, \mathcal{C}$  and a matrix  $M$ , we define the submatrix  $M_{\mathcal{R}, \mathcal{C}}$  as the matrix with entries  $M_{ij}$  for all  $(i, j) \in \mathcal{R} \times \mathcal{C}$  (we also use the Matlab notation “:” to indicate that all entries on a dimension are taken). In particular, for the Hessian  $\nabla_x^2 \mathcal{L}_{\rho_k}(x^{(k)}, y^{(k)})$ , and the Jacobian  $\nabla c(x^{(k)})^T$ , we define the reduced Hessian and Jacobian as

$$H_k := \left[ \nabla_x^2 \mathcal{L}_{\rho_k}(x^{(k)}, y^{(k)}) \right]_{\mathcal{I}^k, \mathcal{I}^k} \quad \text{and} \quad A_k := \left[ \nabla c(x^{(k)})^T \right]_{:, \mathcal{I}^k}. \quad (3.12)$$

We can show that a sufficient condition for  $\nabla^2 \mathcal{L}_{\rho} \succeq 0$  on the active set is

$$\rho \geq \rho_{\min}(\mathcal{A}^k) := \frac{\max\{0, -\lambda_{\min}(H_k)\}}{\sigma_{\min}(A_k)^2}, \quad (3.13)$$

where  $\lambda_{\min}(\cdot)$  and  $\sigma_{\min}(\cdot)$  denote the smallest eigenvalue and singular value, respectively. Computing (3.13) directly would be prohibitive for large-scale problems, and we use the following estimate instead: R.2.15

$$\tilde{\rho}_{\min}(\mathcal{A}^k) := \max \left\{ 1, \frac{\|H_k\|_1}{\max \left\{ \frac{1}{\sqrt{|\mathcal{I}^k|}} \|A_k\|_{\infty}, \frac{1}{\sqrt{m}} \|A_k\|_1 \right\}} \right\}, \quad (3.14)$$

where  $|\mathcal{I}^k|$  is the number of free variables and  $m$  is the number of general equality constraints. If  $\rho_k < \tilde{\rho}_{\min}(\mathcal{A}^k)$ , then we increase the penalty parameter to  $\rho_{k+1} = 2\tilde{\rho}_{\min}(\mathcal{A}^k)$ . We could further improve this estimate by taking the terms  $\rho c_i \nabla^2 c_i$  into account, which would change the numerator in (3.14).

An alternative adaptive penalty update is proposed in [29]. The authors propose an adaptive penalty parameter update to mitigate any initial poor choices of penalty parameter during early iterations.

### 3.2 Switching to Restoration Phase

In practice, many NLPs are not feasible; this situation happens frequently in particular when solving MINLPs. In this case, it is important that the NLP solver quickly and reliably find a minimum of the constraint violation  $\eta(x)^2$ . To converge quickly to such a point, we **have to either** drive the penalty parameter to infinity or switch to the minimization of  $\eta(x)$ . We prefer the latter approach because it provides an easy escape if we determine that the NLP appears to be feasible after all. **We note, that unlike linear programming (LP), there does not exist a phase I/phase II approach for NLPs, because even once we become feasible, subsequent steps cannot be guaranteed to maintain feasibility for general NLP, unlike for LP, where we only need to establish feasibility once in phase I.** R.1

We define a set of implementable criteria that force the algorithm to switch to the minimization of the constraint violation. Recall that the augmented Lagrangian filter implies the existence of an upper bound  $U = \max\{\omega_{\min}/\gamma, \beta\eta_{\min}\}$  from (2.7). Thus any inner iteration that generates R.2.9 and R.1

$$\hat{\eta}_{j+1} = \eta(\hat{x}^{(j+1)}) \geq \beta U \quad (3.15)$$

triggers the restoration phase. The second test that triggers the restoration phase is related to the minimum constraint violation  $\eta_{\min}$  of filter entries. In particular, if it appears that the augmented Lagrangian is converging to a stationary point while the constraint violation is still large, then we switch to the restoration phase, because we take this situation as an indication that the penalty parameter is too small, illustrated by the purple area in Figure 1. This observation motivates the following condition:

$$\omega_{\rho_k}(\hat{x}^{(j+1)}, y^{(k)}) \leq \epsilon \text{ and } \eta(\hat{x}^{(j+1)}) \geq \beta\eta_{\min}, \quad (3.16)$$

where  $\epsilon > 0$  is a constant and  $\eta_{\min}$  is the smallest constraint violation of any filter entry, namely  $\eta_{\min} := \min\{\eta_l : (\eta_l, \omega_l) \in \mathcal{F}\} > 0$ , which is positive because we only ever add entries with positive constraint violation to the filter. In our algorithm, we switch to restoration if (3.15) or (3.16) holds. R.2.10

Each time we switch to restoration, we increase the penalty parameter and start a new major iteration. The outcome of the restoration phase is either a (local) minimum of the infeasibility or a new point that is filter-acceptable. The (approximate) first-order condition for a minimum of the constraint violation  $\eta(x)^2$  at  $\hat{x}^{(j)}$  is:

$$\left\| \min \left( \hat{x}^{(j)} - l, \max \left( \hat{x}^{(j)} - u, 2\nabla c(\hat{x}^{(j)})^T c(\hat{x}^{(j)}) \right) \right) \right\| \leq \epsilon \text{ and } \eta(\hat{x}^{(j)}) > \epsilon, \quad (3.17)$$

where  $\epsilon > 0$  is a constant that represents the optimality tolerance. The mechanism of the algorithm ensures that we either terminate at a first-order point of the constraint violation, or find a point that is acceptable to the filter, because  $\eta_{\min} > 0$ , which is formalized in the following lemma.

**Lemma 3.1.** *Either the restoration phase converges to a minimum of the constraint violation, or it finds a point  $x^{(k+1)}$  that is acceptable to the filter in a finite number of steps.*

**Proof.** The restoration phase minimizes  $\eta(x)^2$  and hence either converges to a local minimum of the constraint violation or generates a sequence of iterates  $x^{(j)}$  with  $\eta(x^{(j)}) \rightarrow 0$ . Because we only add points with  $\eta_l > 0$  to the filter, it follows that  $\eta_l > 0$  for all  $(\eta_l, \omega_l) \in \mathcal{F}_k$  (defined in Algorithm 2), and hence that we must find a filter-acceptable point in a finite number of iterations in the latter case. R.2.11  
R.2.12  $\square$

### 3.3 Termination of Inner Minimization

The filter introduced in Section 2 ensures convergence only to *feasible* limit points; see Lemma 4.4. Thus, we need an additional condition that ensures that the limit points are also first-order optimal. We introduce a sufficient reduction condition that will ensure that the iterates are stationary. A sufficient reduction condition is more natural (since it corresponds to a Cauchy-type condition, which holds for all reasonable optimization routines) than is a condition that explicitly links the progress in first-order optimality  $\omega_k$  to progress toward feasibility  $\eta_k$ .

In particular, we require that the following condition be satisfied at each inner iteration:

$$\Delta \mathcal{L}_{\rho_k}^{(j)} := \mathcal{L}_{\rho_k}(\hat{x}^{(j)}, y^{(k)}) - \mathcal{L}_{\rho_k}(\hat{x}^{(j+1)}, y^{(k)}) \geq \sigma \hat{\omega}_j, \quad (3.18)$$

where  $\sigma > 0$  is a constant. This condition can be satisfied, for example, by requiring Cauchy decrease on the augmented Lagrangian for fixed  $\rho_k$  and  $y^{(k)}$ . We note that the right-hand side of (3.18) is the dual infeasibility error of the augmented Lagrangian at  $\hat{x}^{(j)}$ , which corresponds to the dual infeasibility error of (NLP) after the first-order multiplier update.

We will show that this sufficient reduction condition of the inner iterates in turn implies a sufficient reduction condition of the outer iterates as we approach feasibility; see (4.21). This outer



sufficient reduction leads to a global convergence result. To the best of our knowledge, this is the first time that a more readily implementable sufficient reduction condition has been used in the context of augmented Lagrangians.

### 3.4 Optional Second-Order (EQP) Step

Our algorithm allows for an additional second-order step. The idea is to use the approximate minimizers  $x^{(k)}$  of the augmented Lagrangian to identify the active inequality constraints  $x_i^{(k)} = 0$ , and then solve an equality-constrained QP (EQP) on those active constraints, similarly to popular SLQP approaches. Given sets of active and inactive constraints (3.11), our goal is to solve an EQP with  $x_i^{(k)} = l_i$ , or  $x^{(k)} = u_i, \forall i \in \mathcal{A}^k$ . Provided that the EQP is convex, its solution can be obtained by solving an augmented linear system. R.2.14

Using the notation introduced in (3.11) and (3.12), the convex EQP is equivalent to the following augmented system,

$$\begin{bmatrix} H_k & A_k^T \\ A_k & \end{bmatrix} \begin{pmatrix} \Delta x_{\mathcal{I}} \\ \Delta y \end{pmatrix} = \begin{pmatrix} -\nabla f_{\mathcal{I}}^{(k+1)} \\ -c(x^{(k+1)}) \end{pmatrix}, \quad (3.19)$$

and  $\Delta x_{\mathcal{A}} = 0$ . We note that, in general, we cannot expect that the solution  $x^{(k+1)} + \Delta x$  is acceptable to the filter (or **may not be a descent direction for the augmented Lagrangian**). Hence, we add a backtracking line search to our algorithm to find an acceptable point. We note that because  $(x^{(k+1)}, y^{(k+1)})$  is known to be acceptable, we can terminate the line search if the step size is less than some  $\alpha_{\min} > 0$  and instead accept  $(x^{(k+1)}, y^{(k+1)})$ . R.2.16

### 3.5 Complete Algorithm

A complete description of the method is given in Algorithm 3. It has an inner loop that minimizes the augmented Lagrangian for fixed penalty parameter,  $\rho_k$ , and multipliers,  $y^{(k)}$  until a filter-acceptable point is found. Quantities associated with the inner loop are indexed by  $j$  and have a “hat.” The outer loop corresponds to major iterates and may update the penalty parameter. The inner iteration also terminates when we switch to the restoration phase. Any method for minimizing  $\eta(x)^2$  (or any measure of constraint infeasibility) can be used in this phase. Note that the penalty parameter is also increased every time we switch to the restoration phase, although we could use a more sophisticated penalty update in that case, too. R.1

We note that Algorithm 3 uses a flag, *RestFlag*, to indicate whether we entered the restoration phase or not. If we enter the restoration phase, we increase the penalty parameter in the outer loop iterates  $k$ . Two possible outcomes for the restoration phase exist: either we find a nonzero (local) minimizer of the constraint violation indicating that problem (NLP) is infeasible, or we find a filter-acceptable point and exit the inner iteration. In the latter case, *RestFlag* = *true* ensures that we do not update the penalty parameter using (3.14), which does not make sense in this situation.

## 4 Convergence Proof

This section establishes a global convergence result for Algorithm 3, without the second-order step for the sake of simplicity. We make the following assumptions throughout this section.

**Assumption 4.1.** Consider problem (NLP), and assume that the following hold:

Given  $(x^{(0)}, y^{(0)})$  and  $\rho_0$ , set  $\omega_0 \leftarrow \omega(x^{(0)}, y^{(0)})$ ,  $\eta_0 \leftarrow \eta(x^{(0)})$ ,  $\mathcal{F}_0 \leftarrow \{(\eta_0, \omega_0)\}$ , and  $k \leftarrow 0$   
**while**  $(x^{(k)}, y^{(k)})$  not optimal **do**

  Set  $j \leftarrow 0$ , *RestFlag*  $\leftarrow$  false, and initialize  $\hat{x}^{(0)} \leftarrow x^{(k)}$

**while**  $(\hat{\eta}_j, \hat{\omega}_j)$  not acceptable to  $\mathcal{F}_k$  **do**

    Approximately minimize the augmented Lagrangian for  $\hat{x}^{(j+1)}$  starting at  $\hat{x}^{(j)}$ :

$$\underset{l \leq x \leq u}{\text{minimize}} \quad \mathcal{L}_{\rho_k}(x, y^{(k)}) = f(x) - y^{(k)T} c(x) + \frac{1}{2} \rho_k \|c(x)\|^2$$

    such that the sufficient reduction condition (3.18) holds.

**if** restoration switching condition (3.15) or (3.16) holds **then**

    Set *RestFlag* = true

    Increase penalty parameter:  $\rho_{k+1} \leftarrow 2\rho_k$

    Switch to restoration phase to find  $(\hat{x}^{(j+1)}, \hat{y}^{(j+1)})$  acceptable to  $\mathcal{F}$  or find an infeasible point that minimizes  $\|c(x)\|^2$  subject to  $l \leq x \leq u$

**else**

    Provisionally update multipliers:  $\hat{y}^{(j+1)} \leftarrow y^{(k)} - \rho_k c(\hat{x}^{(j+1)})$

    Compute  $\hat{\omega}_{j+1} \leftarrow \omega_0(\hat{x}^{(j+1)}, \hat{y}^{(j+1)})$  and  $\hat{\eta}_{j+1} \leftarrow \eta(\hat{x}^{(j+1)})$ .

  Set  $j \leftarrow j + 1$

Set  $(\hat{x}^{(k+1)}, \hat{y}^{(k+1)}) \leftarrow (\hat{x}^{(j)}, \hat{y}^{(j)})$

Solve EQP (3.19) for  $(\Delta x^{(k+1)}, \Delta y^{(k+1)})$

Line-search: Find  $\alpha_k \in \{0\} \cup [\alpha_{\min}, 1]$  such that

$$(x^{(k+1)}, y^{(k+1)}) = (\hat{x}^{(k+1)}, \hat{y}^{(k+1)}) + \alpha_k (\Delta x^{(k+1)}, \Delta y^{(k+1)}) \text{ acceptable to } \mathcal{F}_k$$

Compute  $\omega_{k+1} \leftarrow \omega_0(x^{(k+1)}, y^{(k+1)})$ ,  $\eta_{k+1} \leftarrow \eta(x^{(k+1)})$

**if**  $\eta_{k+1} > 0$  **then**

  Add  $(\eta_{k+1}, \omega_{k+1})$  to filter:  $\mathcal{F}_{k+1} \leftarrow \mathcal{F}_k \cup \{(\eta_{k+1}, \omega_{k+1})\}$  (ensuring  $\eta_l > 0 \forall l \in \mathcal{F}_{k+1}$ )

**if** not *RestFlag* and  $\rho_k < \tilde{\rho}_{\min}(\mathcal{A}^k)$  see (3.14) **then**

  Increase penalty:  $\rho_{k+1} \leftarrow 2\tilde{\rho}_{\min}(\mathcal{A}^k)$

**else**

  Leave penalty parameter unchanged:  $\rho_{k+1} \leftarrow \rho_k$

Set  $k \leftarrow k + 1$

**Algorithm 3: Augmented Lagrangian Filter Method.**

**A1** The problem functions  $f, c$  are twice continuously differentiable.

**A2** The constraint norm satisfies  $\|c(x)\| \rightarrow \infty$  as  $\|x\| \rightarrow \infty$ .

Assumption **A1** is standard. Assumption **A2** implies that our iterates remain in a compact set (see Lemma 4.1). This assumption could be replaced by an assumption that we optimize over finite bounds  $l \leq x \leq u$ . Both assumptions together imply that  $f(x)$  and  $c(x)$  and their derivatives are bounded for all iterates.

Algorithm 3 has three distinct outcomes.

1. There exists an infinite sequence of restoration phase iterates  $x^{(k_i)}$ , indexed by  $\mathcal{R} := \{k_1, k_2, \dots\}$ , whose limit point  $x^* := \lim x^{(k_i)}$  minimizes the constraint violation, satisfying  $\eta(x^*) > 0$ ;

2. There exists an infinite sequence of successful major iterates  $x^{(k_l)}$ , indexed by  $\mathcal{S} := \{k_1, k_2, \dots\}$ , and the linear independence constraint qualification fails to hold at the limit  $x^* := \lim x^{(k_l)}$ , which is a Fritz-John (FJ) point of (NLP);
3. There exists an infinite sequence of successful major iterates  $x^{(k_l)}$ , indexed by  $\mathcal{S} := \{k_1, k_2, \dots\}$ , and the linear independence constraint qualification holds at the limit  $x^* := \lim x^{(k_l)}$ , which is a Karush-Kuhn-Tucker point of (NLP).

Outcomes 1 and 3 are normal outcomes of NLP solvers in the sense that we cannot exclude the possibility that (NLP) is infeasible without making restrictive assumptions such as Slater's constraint qualification. Outcome 2 corresponds to the situation where a constraint qualification fails to hold at a limit point.

**Outline of Convergence Proof.** We start by showing that all iterates remain in a compact set. Next, we show that the algorithm is well defined by proving that the inner iteration is finite, which implies the existence of an infinite sequence of outer iterates  $x^{(k)}$ , unless the restoration phase fails or the algorithm converges finitely. We then show that the limit points are feasible and stationary. Finally, we show that the penalty estimate (3.14) is bounded.

We first show that all iterates remain in a compact set.

**Lemma 4.1.** *All major and minor iterates,  $x^{(k)}$  and  $\hat{x}^{(j)}$ , remain in a compact set  $C$ .*

**Proof.** The upper bound  $U$  on  $\eta(x)$  implies that  $\|c(x^{(k)})\| \leq U$  for all  $k$ . The switching condition (3.15) implies that  $\|c(\hat{x}^{(j)})\| \leq U$  for all  $j$ . The feasibility restoration minimizes  $\eta(x)$ , implying that all its iterates in turn satisfy  $\|c(x^{(k)})\| \leq U$ . Assumptions **A1** and **A2** now imply that the iterates remain in a bounded set  $C$ .  $\square$

The next lemma shows that the mechanism of the filter ensures that there exists a neighborhood of the origin in the filter that does not contain any filter points, as illustrated in Figure 1 (right).

**Lemma 4.2.** *There exists a neighborhood of  $(\eta, \omega) = (0, 0)$  that does not contain any filter entries.*

**Proof.** The mechanism of the algorithm ensures that  $\eta_l > 0$ ,  $\forall (\eta_l, \omega_l) \in \mathcal{F}_k$ . First, assume that  $\omega_{\min} := \min\{\omega_l : (\eta_l, \omega_l) \in \mathcal{F}_k\} > 0$ . Then it follows that there exist no filter entries in the quadrilateral bounded by  $(0, 0)$ ,  $(0, \omega_{\min})$ ,  $(\beta\eta_{\min}, \omega_{\min} - \gamma\beta\eta_{\min})$ ,  $(\beta\eta_{\min}, 0)$ , illustrated by the green area in Figure 1 (right). Next, if there exists a filter entry with  $\omega_l = 0$ , then define  $\omega_{\min} := \min\{\omega_l > 0 : (\eta_l, \omega_l) \in \mathcal{F}_k\} > 0$ , and observe that the quadrilateral  $(0, 0)$ ,  $(0, \omega_{\min})$ ,  $(\beta\eta_{\min}, \omega_{\min})$ ,  $(\beta\eta_{\min}, 0)$  contains no filter entries. In both cases, the area is nonempty, thus proving that there exists a neighborhood of  $(0, 0)$  with filter-acceptable points.  $\square$

Next, we show that the inner iteration is finite and the algorithm is well defined.

**Lemma 4.3.** *The inner iteration is finite.*

**Proof.** If the inner iteration finitely terminates with a filter-acceptable point or switches to the restoration phase, then there is nothing to prove. Otherwise, there exists an infinite sequence of inner iterates  $\hat{x}^{(j)}$  with  $\hat{\eta}_j \leq \beta U$ . Lemma 4.1 implies that this sequence has a limit point  $x^* = \lim \hat{x}^{(j)}$ . We note that the penalty parameter and the multipliers are fixed during the inner iteration, and we consider the sequence  $\mathcal{L}_\rho(\hat{x}^{(j)}, y)$  for fixed  $\rho = \rho_k$  and  $y = y^{(k)}$ . The sufficient reduction condition (3.18) implies that

$$\Delta\mathcal{L}_\rho^{(j)} := \mathcal{L}_\rho(\hat{x}^{(j)}, y) - \mathcal{L}_\rho(\hat{x}^{(j+1)}, y) \geq \sigma\hat{\omega}_j.$$

If the first-order error,  $\hat{\omega}_j \geq \bar{\omega} > 0$  is bounded away from zero, then this condition implies that  $\mathcal{L}_\rho(x, y^{(k)})$  is unbounded below, which contradicts the fact that  $f(x), \|c(x)\|$  are bounded by Assumption A1 and Lemma 4.1. Thus, it follows that  $\hat{\omega}_j \rightarrow 0$ . If in addition,  $\hat{\eta}_j \rightarrow \hat{\eta} < \beta\eta_{\min}$ , then we must find a filter-acceptable point in the green region of Figure 1, and terminate finitely. Otherwise,  $\hat{\omega}_j \rightarrow 0$  and  $\hat{\eta}_j \geq \beta\eta_{\min}$ , which triggers the restoration phase after a finite number of steps. In either case, we exit the inner iteration according to Lemma 4.2.  $\square$

The next lemma shows that all limit points of the outer iteration are feasible.

**Lemma 4.4.** *Assume that there exist an infinite number of outer iterations. It follows that  $\eta(x^{(k)}) \rightarrow 0$ .* R.1

**Proof.** Every outer iteration for which  $\eta_k > 0$  adds an entry to the filter. The proof follows directly from [24, Lemma 1].  $\square$

The next two lemmas show that the first-order error  $\omega_k$  also converges to zero. We split the argument into two parts depending on whether the penalty parameter remains bounded or not.

**Lemma 4.5.** *Assume that the penalty parameter is bounded,  $\rho_k \leq \bar{\rho} < \infty$ , and consider an infinite sequence of outer iterations. Then it follows that  $\omega(x^{(k)}) \rightarrow 0$ .*

**Proof.** Because the penalty parameter is bounded, it is updated only finitely often. Hence, we consider the tail of the sequence  $x^{(k)}$  for which the penalty parameter has settled down, namely  $\rho_k = \bar{\rho}$ . We assume that  $\omega_k \geq \bar{\omega} > 0$  and seek a contradiction. The sufficient reduction condition of the inner iteration (3.18) implies that

$$\Delta\mathcal{L}_{\bar{\rho},k}^{\text{in}} := \mathcal{L}_{\bar{\rho}}(x^{(k)}, y^{(k)}) - \mathcal{L}_{\bar{\rho}}(x^{(k+1)}, y^{(k)}) \geq \sigma\omega_k \geq \sigma\bar{\omega} > 0. \quad (4.20)$$

We now show that this ‘‘inner’’ sufficient reduction (for fixed  $y^{(k)}$ ) implies an ‘‘outer’’ sufficient reduction. We combine (4.20) with the first-order multiplier update (1.4) and obtain

$$\Delta\mathcal{L}_{\bar{\rho},k}^{\text{out}} := \mathcal{L}_{\bar{\rho}}(x^{(k)}, y^{(k)}) - \mathcal{L}_{\bar{\rho}}(x^{(k+1)}, y^{(k+1)}) = \Delta\mathcal{L}_{\bar{\rho},k}^{\text{in}} - \bar{\rho}\|c(x^{(k+1)})\|_2^2 \geq \sigma\bar{\omega} - \bar{\rho}\eta_{k+1}^2. \quad (4.21)$$

Lemma 4.4 implies that  $\eta_k \rightarrow 0$ ; hence, as soon as  $\eta_{k+1} \leq \sigma\frac{\bar{\omega}}{2\bar{\rho}}$  for all  $k$  sufficiently large, we obtain the following sufficient reduction condition for the outer iteration:

$$\Delta\mathcal{L}_{\bar{\rho},k}^{\text{out}} \geq \sigma\frac{\bar{\omega}}{2},$$

for all  $k$  sufficiently large. Thus, if  $\omega_k \geq \bar{\omega} > 0$  is bounded away from zero, then it follows that the augmented Lagrangian must be unbounded below. However, because all  $x^{(k)} \in C$  remain in a compact set, it follows from Assumption A1 that  $f(x)$  and  $\|c(x)\|$  are bounded below and hence that  $\mathcal{L}_{\bar{\rho}}(x, y)$  can be unbounded below only if  $-y^T c(x)$  is unbounded below.

We now show **by construction that there exists a constant  $M > 0$  such that  $c(x^{(k)})^T y^{(k)} \leq M$**  R.1 and R.2.19 for all major iterates. The first-order multiplier update implies that  $y^{(k)} = y^{(0)} - \bar{\rho} \sum_{l=1}^k c^{(l)}$  and hence that

$$c(x^{(k)})^T y^{(k)} = \left( y^{(0)} - \bar{\rho} \sum_{l=1}^k c^{(l)} \right)^T c^{(k)} \leq \left( \|y^{(0)}\| + \bar{\rho} \sum_{l=1}^k \|c^{(l)}\| \right) \|c^{(k)}\| = \left( y_0 + \bar{\rho} \sum_{l=1}^k \eta_l \right) \eta_k, \quad (4.22)$$

where  $y_0 = \|y^{(0)}\|$ , and we have assumed without loss of generality that  $\bar{\rho}$  is fixed for the whole sequence. Now define  $E_k := \max_{l \geq k} \eta_l$  and observe that  $E_k \rightarrow 0$  from Lemma 4.4. The definition of the filter then implies that  $E_{k+1} \leq \beta E_k$ , and we obtain from (4.22) that

$$c(x^{(k)})^T y^{(k)} \leq \left( y_0 + \bar{\rho} \sum_{l=1}^k E_l \right) E_k = \left( y_0 + \bar{\rho} \sum_{l=1}^k \beta^l E_0 \right) \beta^k E_0 = \left( y_0 + \bar{\rho} \beta \frac{1 - \beta^k}{1 - \beta} E_0 \right) \beta^k E_0 < M.$$

Moreover, because  $E_0 < \infty$ ,  $\bar{\rho} < \infty$  and  $0 < \beta < 1$ , it follows that this expression is uniformly bounded as  $k \rightarrow \infty$ . Hence  $c(x^{(k)})^T y^{(k)} \leq M$  for all  $k$ , and  $\mathcal{L}_{\bar{\rho}}(x, y)$  must be bounded below, which contradicts the assumption that  $\omega_k \geq \bar{\omega} > 0$  is bounded away from zero. It follows that  $\omega_k \rightarrow 0$ .  $\square$

We now consider the case where  $\rho_k \rightarrow \infty$ . In this case, we must assume that the linear independence constraint qualification (LICQ) holds at every limit point. If LICQ fails at a limit point, then we cannot guarantee that the limit is a KKT point; it may be a Fritz-John point instead. The following lemma formalizes this result.

**Lemma 4.6.** *Consider the situation where  $\rho_k \rightarrow \infty$ . Then any limit point  $x^{(k)} \rightarrow x^*$  is a Fritz-John point. If in addition LICQ holds at  $x^*$ , then it is a KKT point, and  $\omega_k \rightarrow 0$ .*

**Proof.** Lemma 4.4 ensures that the limit point is feasible. Hence, it is trivially a Fritz-John point. Now assume that LICQ holds at  $x^*$ . We use standard augmented Lagrangian theory to show that this limit point also satisfies  $\omega(x^*) = 0$ . Following Theorem 2.5 of [41], we need to show that for all restoration iterations  $\mathcal{R} := \{k_1, k_2, k_3, \dots\}$  on which we increase the penalty parameter, it follows that the quantity

$$\sum_{l=1}^{\infty} \eta_{k_\nu + l}$$

remains bounded as  $\nu \rightarrow \infty$ . Similarly to the proof of Lemma 4.5, the filter acceptance ensures that  $\eta_{k_\nu + l} \leq \beta^l \eta_{k_\nu}$ , which gives the desired result. Thus, we can invoke Theorem 2.5 of [41], which shows that the limit point is a KKT point.  $\square$

The preceding lemmas are summarized in the following result.

**Theorem 4.1.** *Assume that Assumptions A1 and A2 hold. Then either Algorithm 3 terminates after a finite number of iterations at a KKT point, that is, for some finite  $k$ ,  $x^{(k)}$  is a first-order stationary point with  $\eta(x^{(k)}) = 0$  and  $\omega(x^{(k)}) = 0$ , or there exists an infinite sequence of iterates  $x^{(k)}$  and any limit point  $x^{(k)} \rightarrow x^*$  that satisfy one of the following:*

1. *The penalty parameter is updated finitely often, and  $x^*$  is a KKT point;*
2. *There exists an infinite sequence of restoration steps at which the penalty parameter is updated. If  $x^*$  satisfies LICQ, then it is a KKT point. Otherwise, it is an FJ point;*
3. *The restoration phase converges to a minimum of the constraint violation.*

**Remark 4.1.** *We seem to be able to show that the limit point is a KKT point without assuming a constraint qualification, as long as the penalty parameter remains bounded. On the other hand, without a constraint qualification, we would expect the penalty parameter to be unbounded. It would be interesting to test these results in the context of mathematical programs with equilibrium constraints (MPECs). We suspect that MPECs that satisfy a strong-stationarity condition would have a bounded penalty, but that those that do not have strongly stationary points would require the penalty to be unbounded.*

**Remark 4.2.** *The careful reader may wonder whether Algorithm 3 can cycle, because we do not add iterates to the filter for which  $\eta_k = 0$ . We can show, however, that this situation cannot happen. If we have an infinite sequence of iterates for which  $\eta_k = 0$ , then the sufficient reduction condition (3.18) implies that we must converge to a stationary point, similarly to the arguments in Lemma 4.5. If we have a sequence that alternates between iterates for which  $\eta_k = 0$  and iterates for which  $\eta_k > 0$ , then we can never revisit any iterates for which  $\eta_k > 0$  because those iterates have been added to the filter. By Lemma 4.4, any limit point is feasible. Thus, if LICQ holds, then the limit is a KKT point; otherwise, it may be an FJ point. We note that these conclusions are consistent with Theorem 4.1.*

## 5 Numerical Results

We have implemented a preliminary version of Algorithm 3 in C++, using L-BFGS-B 3.0, see [73], to minimize the bound-constrained augmented Lagrangian and MA57, see [32], to solve the reduced KKT system. All experiments are run on a Lenovo Thinkpad X1 Carbon with an Intel Core i7 processor running at 2.6GHz and 16Gb RAM under the Ubuntu 18.04.2 LTS operating system. R.Ed




Figure 2: Distribution of CUTEst test problems based on number of variables,  $n$ , and number of constraints,  $m$ .

We have chosen 429 small test problems from the CUTEst test set [47] that have up to 100 variables and/or constraints. The distribution of the problem sizes is shown in Figure 2. We compare the performance of our filter augmented Lagrangian method, referred to as filter-al, with five other state-of-the-art NLP solvers:

- FilterSQP [36] is a filter SQP solver endowed with a trust-region mechanism to enforce convergence;
- SNOPT [45] is an SQP method using limited-memory quasi-Newton approximations to the Hessian of the Lagrangian with an augmented Lagrangian merit function;
- MINOS [59] implements a linearly-constrained augmented Lagrangian method with a line-search mechanism;
- IPOPT [71] implements a filter interior-point method with a line-search mechanism; and,

- LANCELOT [26] is a bound-constrained augmented Lagrangian method.

Because the test problems are small and our implementation is still preliminary, we only compare the number of gradient evaluation to solve a problem. This statistic is a good surrogate for the number of major iterations. Detailed results are shown in Table 1 in the appendix. We note, that MINOS and SNOPT do not report gradient evaluations for some problems such as QPs, which results in empty entries in the table. In these cases, we set the number of gradient evaluations to “1”, which favors these solvers slightly, but does not change our overall conclusions.




Figure 3: Performance profile comparing number of gradient evaluations of different NLP solvers for 429 small CUTEst problems.

We summarize our numerical results using a performance profile, [30], in Figure 3. We observe that filter-al is competitive with the two SQP solvers, FilterSQP and SNOPT, which typically require the smallest number of iterations. This result is very encouraging, because whilst filter-al can in principle be parallelized by using parallel subproblem solvers, parallelizing an SQP method is significantly harder. Moreover, our new solver, filter-al, clearly outperforms the two augmented Lagrangian methods, MINOS and LANCELOT, indicating that the use of a filter provides a faster convergence mechanism, reducing the number of iterations.

## 6 Conclusions

We have introduced a new filter strategy for augmented Lagrangian methods that removes the need for the traditional forcing sequences. We prove convergence of our method to first-order stationary points of nonlinear programs under mild conditions, and we present a heuristic for adjusting the penalty parameter based on matrix-norm estimates. We show that second-order steps are readily integrated into our method to accelerate local convergence.

The proposed method is closely related to Newton’s method in the case of equality constraints only. If no inequality constraints exist, that is if  $x$  is unrestricted in (NLP), then our algorithm

reverts to standard Newton/SQP for equality constrained optimization with a line-search safeguard. In this case, we only need to compute the Cauchy point to the augmented Lagrangian step that is acceptable to the filter. Of course, a more direct implementation would be preferable.

Our proof leaves open a number of questions. First, we did not show second-order convergence, but we believe that such a proof follows directly if we use second-order correction steps as suggested in [69], or if we employ a local non-monotone filter similar to [66]. A second open question is how the proposed method performs in practice. We have some promising experience with large-scale quadratic programs [42], and we are working on an implementation for nonlinear programs.

We have presented preliminary numerical results on 429 small CUTEst test problems that showed that our new augmented Lagrangian filter method outperforms other augmented Lagrangian solvers, and is competitive with SQP methods in terms of major iterations.

## Acknowledgments

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of Advanced Scientific Computing Research, under Contract DE-AC02-06CH11357. This work was also supported by the U.S. Department of Energy through grant DE-FG02-05ER25694.

## References

- [1] Kumar Abhishek, Sven Leyffer, and Jeffrey T. Linderoth. FilmINT: An outer-approximation-based solver for nonlinear mixed integer programs. *INFORMS Journal on Computing*, 22:555–567, 2010.
- [2] A. Altay-Salih, M.C. Pinar, and S. Leyffer. Constrained nonlinear programming for volatility estimation with GARCH models. *SIAM Review*, 45(3):485–503, 2003.
- [3] J.J. Arrieta-Camacho, L.T. Biegler, and D. Subramanian. NMPC-based real-time coordination of multiple aircraft. In R.F. Allgower and L.T. Biegler, editors, *Assessment and Future Directions of Nonlinear Model Predictive Control*, pages 629–639. Springer, Heidelberg, 2007.
- [4] Guillermo Bautista, Miguel F. Anjos, and Anthony Vannelli. Formulation of oligopolistic competition in AC power networks: An NLP approach. *IEEE Transaction on Power Systems*, 22(1):105–115, 2007.
- [5] Pietro Belotti, Christian Kirches, Sven Leyffer, Jeff Linderoth, James Luedtke, and Ashutosh Mahajan. Mixed-integer nonlinear optimization. *Acta Numerica*, 22:1–131, 5 2013.
- [6] Hande Benson and David Shanno. An exact primal-dual penalty method approach to warm-starting interior-point methods for linear programming. *Computational Optimization and Applications*, 38:371–399, 2007. 10.1007/s10589-007-9048-6.
- [7] Hande Y. Benson and David F. Shanno. Interior-point methods for nonconvex nonlinear programming: regularization and warmstarts. *Computational Optimization and Applications*, 40(2):143–189, 2008.
- [8] H.Y. Benson, D.F. Shanno, and R.J. Vanderbei. Interior-point methods for nonconvex nonlinear programming: filter-methods and merit functions. *Computational Optimization and Applications*, 23(2):257–272, 2002.



- [9] D.P. Bertsekas. *Constrained Optimization and Lagrange Multiplier Methods*. Athena Scientific, New York, 1982.
- [10] J.T. Betts. *Practical Methods for Optimal Control Using Nonlinear Programming*. Advances in Design and Control. SIAM, Philadelphia, 2001.
- [11] L.T. Biegler and I.E. Grossmann. Challenges and research issues for product and process design optimization. In C.A. Floudas and R. Agrawal, editors, *Proceedings of Foundations of Computer Aided Process Design*. CACHE Corporation, Austin, TX, 2004.
- [12] L.T. Biegler and I.E. Grossmann. Part I: Retrospective on optimization. *Computers and Chemical Engineering*, 28(8):1169–1192, 2004.
- [13] E.G. Birgin and J.M. Martinez. Improving ultimate convergence of an augmented Lagrangian method. *Optimization Methods and Software*, 23(2):177–195, 2008.
- [14] P. Bonami, L.T. Biegler, A.R. Conn, G. Cornuejols, I.E. Grossmann, C.D. Laird, J. Lee, A. Lodi, F. Margot, N. Sawaya, and A. Wächter. An algorithmic framework for convex mixed integer nonlinear programs. Research Report RC 23771, IBM T. J. Watson Research Center, Yorktown, NY, 2005.
- [15] Pierre Bonami, Jon Lee, Sven Leyffer, and Andreas Waechter. More branch-and-bound experiments in convex nonlinear integer programming. Technical Report ANL/MCS-P1949-0911, Argonne National Laboratory, Mathematics and Computer Science Division, Lemont, IL, September 2011.
- [16] J.F. Bonnans and J. André. Optimal structure of gas transmission trunklines. Technical Report 6791, INRIA Saclay, 91893 ORSAY Cedex, France, 2009.
- [17] B. Bonnard, L. Faubourg, G. Launay, and E. Trélat. Optimal control with state constraints and the space shuttle re-entry problem. *Journal of Dynamical and Control Systems*, 9(2):155–199, 2003.
- [18] A. Borghetti, A. Frangioni, F. Lacalandra, and C.A. Nucci. Lagrangian heuristics based on disaggregated bundle methods for hydrothermal unit commitment. *IEEE Transactions on Power Systems*, 18:1–10, 2003.
- [19] R.H. Byrd, N.I.M. Gould, J. Nocedal, and R.A. Waltz. An algorithm for nonlinear optimization using linear programming and equality constrained subproblems. *Mathematical Programming, Series B*, 100(1):27–48, 2004.
- [20] R.H. Byrd, M.E. Hribar, and J. Nocedal. An interior point algorithm for large scale nonlinear programming. *SIAM J. Optimization*, 9(4):877–900, 1999.
- [21] R.H. Byrd, J. Nocedal, and R.A. Waltz. KNITRO: An integrated package for nonlinear optimization. In G. di Pillo and M. Roma, editors, *Large-Scale Nonlinear Optimization*, pages 35–59. Springer-Verlag, New York, 2006.
- [22] Calamai, P.H. and Moré, J.J. Projected gradient methods for linearly constraint problems. *Mathematical Programming*, 39:93–116, 1987.
- [23] J. Castro and J.A. Gonzalez. A nonlinear optimization package for long-term hydrothermal coordination. *European Journal of Operational Research*, 154(1):641–658, 2004.

- [24] C.M. Chin and R. Fletcher. On the global convergence of an SLP-filter algorithm that takes EQP steps. *Mathematical Programming*, 96(1):161–177, 2003.
- [25] T.F. Coleman, Y. Li, and A. Verman. Reconstructing the unknown volatility function. *Journal of Computational Finance*, 2(3):77–102, 1999.
- [26] A.R. Conn, N.I.M. Gould, and Ph.L. Toint. *LANCELOT: A Fortran package for large-scale nonlinear optimization (Release A)*. Springer Verlag, Heidelberg, New York, 1992.
- [27] A.R. Conn, N.I.M. Gould, and Ph.L. Toint. *Trust-Region Methods*. MPS-SIAM Series on Optimization. SIAM, Philadelphia, 2000.
- [28] G. Cornuejols and R. Tütüncü. *Optimization Methods in Finance*. Cambridge University Press, 2007.
- [29] Frank E Curtis, Hao Jiang, and Daniel P Robinson. An adaptive augmented Lagrangian method for large-scale constrained optimization. *Mathematical Programming*, 152(1-2):201–245, 2015.
- [30] Elizabeth D. Dolan and Jorge Moré. Benchmarking optimization software with performance profiles. *Mathematical Programming*, 91(2):201–213, 2002.
- [31] V. Donde, V. Lopez, B. Lesieutre, A. Pinar, C. Yang, and J. Meza. Identification of severe multiple contingencies in electric power networks. In *Proceedings 37th North American Power Symposium*, 2005. LBNL-57994.
- [32] Iain S Duff. Ma57—a code for the solution of sparse symmetric definite and indefinite systems. *ACM Transactions on Mathematical Software (TOMS)*, 30(2):118–144, 2004.
- [33] Klaus Ehrhardt and Marc C. Steinbach. Nonlinear optimization in gas networks. In H.G. Bock, E. Kostina, H.X. Phu, and R. Ranacher, editors, *Modeling, Simulation and Optimization of Complex Processes*, pages 139–148. Springer, Berlin, 2005.
- [34] R. Fletcher and S. Leyffer. Solving mixed integer nonlinear programs by outer approximation. *Mathematical Programming*, 66:327–349, 1994.
- [35] R. Fletcher and S. Leyffer. User manual for filterSQP. Numerical Analysis Report NA/181, University of Dundee, April 1998.
- [36] R. Fletcher and S. Leyffer. Nonlinear programming without a penalty function. *Mathematical Programming*, 91:239–270, 2002.
- [37] R. Fletcher and S. Leyffer. Filter-type algorithms for solving systems of algebraic equations and inequalities. In G. di Pillo and A. Murli, editors, *High Performance Algorithms and Software for Nonlinear Optimization*, pages 259–278. Kluwer, Dordrecht, 2003.
- [38] R. Fletcher, S. Leyffer, and Ph.L. Toint. On the global convergence of a filter-SQP algorithm. *SIAM J. Optimization*, 13(1):44–59, 2002.
- [39] Fletcher, R. and Sainz de la Maza, E. Nonlinear programming and nonsmooth optimization by successive linear programming. *Mathematical Programming*, 43:235–256, 1989.
- [40] A. Forsgren, P.E. Gill, and M.H. Wright. Interior methods for nonlinear optimization. *SIAM Review*, 4(4):525–597, 2002.

- [41] Michael P. Friedlander. *A Globally Convergent Linearly Constrained Lagrangian Method for Non-linear Optimization*. Ph.D. thesis, Stanford University, August 2002.
- [42] M.P. Friedlander and S. Leyffer. Global and finite termination of a two-phase augmented Lagrangian filter method for general quadratic programs. *SIAM J. Scientific Computing*, 30(4):1706–1729, 2008.
- [43] L.E. Ghaoui, M. Oks, and F. Oustry. Worst-case value-at-risk and robust portfolio optimization: A conic programming approach. *Operations Research*, 51(4), 2003.
- [44] P.E. Gill, W. Murray, and M.A. Saunders. User’s guide for SQOPT 5.3: A Fortran package for large-scale linear and quadratic programming. Tech. Rep. NA 97-4, Department of Mathematics, University of California, San Diego, 1997.
- [45] P.E. Gill, W. Murray, and M.A. Saunders. SNOPT: An SQP algorithm for large-scale constrained optimization. *SIAM Journal on Optimization*, 12(4):979–1006, 2002.
- [46] Jacek Gondzio and Andreas Grothey. Reoptimization with the primal-dual interior point method. *SIAM Journal on Optimization*, 13(3):842–864, 2002.
- [47] Nicholas IM Gould, Dominique Orban, and Philippe L Toint. Cutest: a constrained and unconstrained testing environment with safe threads for mathematical optimization. *Computational Optimization and Applications*, 60(3):545–557, 2015.
- [48] J.-P. Goux and S. Leyffer. Solving large MINLPs on computational grids. *Optimization and Engineering*, 3:327–346, 2002.
- [49] Q. Huangfu and J.A.J. Hall. Novel update techniques for the revised simplex method. Technical Report ERGO-13-001, The School of Mathematics, University of Edinburgh, Edinburgh, UK, 2013.
- [50] Y. Kawayir, C. Laird, and A. Wächter. Introduction to Ipopt: A tutorial for downloading, installing, and using Ipopt. Manual, IBM T.J. Watson Research Center, Yorktown Heights, NY, 2009.
- [51] H. Konno and H. Yamazaki. Mean-absolute deviation portfolio optimization model and its application to Tokyo stock market. *Management Science*, 37:519–531, 1991.
- [52] S. Leyffer. Integrating SQP and branch-and-bound for mixed integer nonlinear programming. *Computational Optimization & Applications*, 18:295–309, 2001.
- [53] S. Leyffer, G. Lopez-Calva, and J. Nocedal. Interior methods for mathematical programs with complementarity constraints. *SIAM Journal on Optimization*, 17(1):52–77, 2006.
- [54] S. Leyffer and T.S. Munson. A globally convergent filter method for MPECs. Preprint ANL/MCS-P1457-0907, Argonne National Laboratory, Mathematics and Computer Science Division, September 2007.
- [55] Miles Lubin, J.A.J. Hall, Cosmin G. Petra, and Mihai Anitescu. Parallel distributed-memory simplex for large-scale stochastic LP problems. *Computational Optimization and Applications*, 55(3):571–596, 2013.
- [56] A. Martin, M. Möller, and S. Moritz. Mixed integer models for the stationary case of gas network optimization. *Mathematical Programming*, 105:563–582, 2006.

- [57] J.A. Momoh, R.J. Koessler, M.S. Bond, B. Stott, D. Sun, A. Papalexopoulos, and P. Ristanovic. Challenges to optimal power flow. *IEEE Transaction on Power Systems*, 12:444–455, 1997.
- [58] J.J. Moré and G. Toraldo. On the solution of quadratic programming problems with bound constraints. *SIAM Journal on Optimization*, 1(1):93–113, 1991.
- [59] B.A. Murtagh and M.A. Saunders. MINOS 5.4 user’s guide. Report SOL 83-20R, Department of Operations Research, Stanford University, 1993.
- [60] Bruce A. Murtagh and Michael A. Saunders. A projected Lagrangian algorithm and its implementation for sparse nonlinear constraints. In A.G. Buckley and J.-L. Goffin, editors, *Algorithms for Constrained Minimization of Smooth Nonlinear Functions*, volume 16 of *Mathematical Programming Studies*, pages 84–117. Springer Berlin Heidelberg, 1982.
- [61] P. Penfield, R. Spence, and S. Duinker. *Tellegen’s theorem and electrical networks*. MIT Press, Cambridge, London, 1970.
- [62] M.J.D. Powell. Algorithms for nonlinear constraints that use Lagrangian functions. *Mathematical Programming*, 14(1):224–248, 1978.
- [63] Gad Rabinowitz, Abraham Mehrez, and Gideon Oron. A nonlinear optimization model of water allocation for hydroelectric energy production and irrigation. *Management Science*, 34(8):973–990, 1988.
- [64] A. Raghunathan and L. T. Biegler. An interior point method for mathematical programs with complementarity constraints (MPCCs). *SIAM Journal on Optimization*, 15(3):720–750, 2005.
- [65] G.B. Sheble and G.N. Fahd. Unit commitment literature synopsis. *IEEE Transactions on Power Systems*, 9:128–135, 1994.
- [66] Chungen Shen, Sven Leyffer, and Roger Fletcher. A nonmonotone filter method for nonlinear optimization. *Computational Optimization and Applications*, 52(3):583–607, 2012.
- [67] E. Smith and J.A.J. Hall. A high performance primal revised simplex solver for row-linked block angular linear programming problems. Technical Report ERGO-12-003, The School of Mathematics, University of Edinburgh, Edinburgh, UK, 2012.
- [68] R.J. Vanderbei and D.F. Shanno. An interior point algorithm for nonconvex nonlinear programming. *COAP*, 13:231–252, 1999.
- [69] A. Wächter and L.T. Biegler. Line search filter methods for nonlinear programming: Local convergence. *SIAM Journal on Optimization*, 16(1):32–48, 2005.
- [70] A. Wächter and L.T. Biegler. Line search filter methods for nonlinear programming: Motivation and global convergence. *SIAM Journal on Optimization*, 16(1):1–31, 2005.
- [71] Andreas Wächter and Lorenz T Biegler. On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming. *Mathematical programming*, 106(1):25–57, 2006.
- [72] R.S. Womersley and K. Lau. Portfolio optimisation problems. In R.L. May and A.K. Easton, editors, *Computational Techniques and Applications: CTAC95*, pages 795–802. World Scientific Publishing Co., 1996.

- [73] Ciyou Zhu, Richard H Byrd, Peihuang Lu, and Jorge Nocedal. Algorithm 778: L-bfgs-b: Fortran subroutines for large-scale bound-constrained optimization. *ACM Transactions on Mathematical Software (TOMS)*, 23(4):550–560, 1997.

## A Appendix

Table 1: Number of evaluations of nonlinear solvers on a subset of CUTEr problems.

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
3pk	3	7		12	210	47
aircrfta	8	4	4	4	8	10
aircrftb	13	21	58	19	66	27
airport	50	13	58	16	528	69
aljazzaf	6	15	145	82	65	24
allinitc	64	24	105	44	56	76
allinit	15	11	17	19	30	13
allinitu	15	12	14	15	21	15
alsotame	3	5	6	9	12	11
argauss	3	1	9		17	13
arglinb	3	2		3	9	2
arglinc	3	2		3	9	2
avgasa	9	2		10	20	12
avgasb	21	2		13	16	11
avion2		19	19	143	18	787
bard	42	11	23	9	37	15
batch		9	33	34	380	1000
beale		10	15	19	25	21
biggs3	12	11	24	28	32	40
biggs5	48	50	107	36	39	64
biggs6	62	83	120	50	120	103
biggsc4	16	2		35	17	15
booth	3	2		2		3
box2	3	9	10	9	11	20
box3	12	8	24	15	16	31
bqp1var	2	2		6	6	3
bqpgabim	3	2		21	108	6
bqpgasim	3	2		21	122	6
brkmcc	6	4	10	4	14	7
brownal	15	8	21	8	78	24
brownbs	57	48	32	8	36	7
brownden	21	9	40	9	42	9
bt10	11	7	23	7	11	20
bt11	16	7	12	9	57	22
bt12	12	5	10	5	60	11
bt13	74	48	33	25	207	1001
bt1	62	1	12	15	17	19
bt2	93	13	18	13	386	36
bt3	3	2		2	13	6
bt4	23	11	10	10	48	25
bt5	27	9	11	8	173	20

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
bt6	118	12	14	18	118	25
bt7	634	19	36	30	86	49
bt8	92	12	14	52	22	30
bt9	36	23	28	14	78	22
byrdsphr	189	11	200	19	97	43
camel6	8	8	19	11	25	8
cantilvr	29	16	27	12	176	27
catena	254	13	145	7	418	56
cb2	25	7	12	9	78	18
cb3	16	7	16	10	72	18
chaconn1	33	5	12	7	55	12
chaconn2	9	5	7	7	55	11
chebyqad		50	3	168	6	62
chnrosnb	40	59	170	92	593	68
cliff	26	28	28	24	47	28
cluster	18	10	9	10	22	45
concon	100	5	8	10	1	676
congigmz	131	4	23	33	43	30
coolhans	15	3	12	10	7	281
core1		6	12	105	151	1001
coshfun	1274	303	233	1039	2508	154
cresc4		52	93	269	865	1001
csfi1	317	18	48	12	10	155
csfi2	57	8	84	86	10	180
cube	10	41	42	58	67	52
dallass	586	56	109	29	141	1001
deconvb	8	30	103	5705	31	31
deconvc	85	58	81	99	88	43
deconvu	45	971	152	687	31	69
degenlpa		2		29		25
degenlpb		2		41		45
demymalo	45	8	18	12	95	28
denschna	9	7	12	7	24	13
denschnb	9	10	10	25	18	11
denschnc	9	11	21	11	31	13
denschnnd	29	43	77	27	112	65
denschne	15	11	44	25	35	16
denschnf	9	7	12	7	22	8
dipigri	1508	13	23	22	130	63
disc2	243	25	522	48	706	20
discs		40	4893	186	629	422
dixchlng	404	12	31	11	1582	44
dixon3dq	3	2		2	44	4
djtl	84	29	1345	861	89	100
dnieper	9	4	13	31	37	75
dual1	3	2	221	17	278	9
dual2	3	2	116	14	216	9

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
dual4	3	2	31	14	209	8
dualc1		2		30	25	17
dualc2		2		28	15	19
dualc5	136	2		11	25	8
dualc8		2		13	17	24
eg1	6	8	9	8	15	9
eigencco	45	29	34	14	159	17
eigmaxc	80	7	11	7	373	21
eigminc	30	7	10	8	120	11
engval2	48	20	34	33	67	30
errinros	22	53	267	70	553	76
expfita	36	13	24	31	29	54
expfit		13	18	9	29	11
extrasim	3	2		6		3
extrosnb	1	2	2	1	6	1
fccu	3	4		2	49	13
fletcher	46	1	2	28	9	28
genhs28	3	2		2	13	5
genhumps	63	188	77	321	170	134
gigomez1	143	8	17	19	141	33
goffin	11	3		10		10
gottfr	16	13	8	9	10	35
gridnetg	24	4	22	11	43	21
gridneth	14	5	36	7	115	20
gridneti	19	5	47	14	112	22
growthls	49	106	184	171	259	178
growth	49	106	187	171	259	178
gulf	33	26	66	44	696	63
hadamals	21	13	19	128	267	20
haifas	728	13	23	10	144	27
hairy	17	84	35	96	60	102
haldmads	23536	41	12	23	129	45
hart6	8	11	16	14	37	9
hatflda	30	15	30	11	45	47
hatfldb	27	11	28	11	33	28
hatfldc	9	5	14	6	20	9
hatfldd	18	23	29	27	49	66
hatflde	18	26	31	32	64	57
hatfldf	246	15	4148	1335	12	113
hatfldg	829	15	17	20	11	29
hatfldh	3	2		19	9	13
heart6ls	20	1001	1351	1588	22799	1001
heart6		16	401	3002	129	1001
heart8ls	445	217	1313	189	475	238
heart8		12	133	40	157	359
helix	9	19	28	25	54	18
hilberta	3	2		2	13	60



Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
hilbertb	3	2		2	113	5
himmelba	3	2		2		3
himmelbb	12	25	8	12	21	11
himmelbc	10	8	7	9	9	11
himmelbd		4	27	79	64	52
himmelbe	15	2	2	3	3	8
himmelbf	14	8	53	11	48	29
himmelbg	10	10	12	14	18	16
himmelbh	6	8	10	24	11	7
himmelbk		6	11	19	172	206
himmelp1	12	9	19	12	21	29
himmelp2	230	9	32	19	152	275
himmelp3	690	5	8	13	120	870
himmelp4	1204	5	8	25	116	737
himmelp5	2680	12	44	543	76	273
himmelp6	208	2	2	12	6	2
hong	6	5	4	13	15	6
hs001	8	36	48	53	10	41
hs002		9	15	17	13	7
hs003	3	2		5	13	16
hs004	2	3	4	6	7	2
hs005	9	11	9	9	14	9
hs006	117	3	9	7	91	63
hs007	24	13	30	28	65	26
hs008	14	6	6	6	8	13
hs009	30	5	10	6	12	22
hs010	31	10	31	13	59	18
hs011	12	6	15	9	47	16
hs012	72	8	11	9	159	26
hs013	79	34	17	79	54	60
hs014	10	6	10	8	10	13
hs015	28	7	11	21	86	47
hs016	19	5	5	23	10	19
hs017	42	8	19	18	12	20
hs018	295	7	32	27	94	117
hs019	39	7	9	16	57	45
hs020	12	5	5	7	9	23
hs021	3	2		9	9	3
hs022	9	2	7	7	48	10
hs023	370	7	7	12	54	51
hs024	6	3	8	13	9	14
hs025	1	27	2	44	6	1
hs026	230	18	27	26	77	41
hs027	18	8	21	143	137	31
hs028	3	2		2	13	4
hs029	77	8	14	9	174	18
hs030	6	2	5	26	30	8

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
hs031	10	6	11	8	29	12
hs032	6	2	5	20	15	7
hs033	9	5	9	16	39	9
hs034	15	8	7	10	33	21
hs035	3	2		8	13	8
hs036	6	3	10	13	9	7
hs037	9	6	10	13	17	13
hs038	7	54	101	78	89	56
hs039	36	23	28	14	78	22
hs040	10	5	9	4	22	11
hs041	6	2	7	12	6	7
hs042	9	6	10	7	22	13
hs043	37	11	11	10	103	25
hs044	3	2		20	11	11
hs045	1	2	2	48	6	1
hs046	53	19	32	20	122	28
hs047	335	21	28	21	126	29
hs048	3	2		2	17	3
hs049	30	17	34	20	62	38
hs050	15	9	20	10	25	11
hs051	3	2		2	13	10
hs052	3	2		2	12	6
hs053	3	2		7	13	6
hs054	3	2		8	17	9
hs055	14	2	2	4	6	7
hs056	22	19	52	40	53	12
hs057	9	5	62	28	29	2
hs059	1000	11	22	72	128	340
hs060	35	7	13	8	121	18
hs061	24	1	39	10	71	19
hs062	53	10	16	9	19	37
hs063	180	1	18	8	120	21
hs064	30	13	28	18	99	38
hs065	169	5	11	91	320	42
hs066	9	14	6	8	21	11
hs067	6234	12	32	12	61	287
hs070	149	42	34	36	67	39
hs071	21	6	8	9	56	16
hs072	30	15	35	17	153	65
hs073	8	4	7	9	16	18
hs074	1274	6	15	10	28	13
hs075	12	5	12	10	19	110
hs076	3	2		8	14	9
hs077	54	14	16	13	124	27
hs078	27	5	7	5	58	12
hs079	40	5	12	5	55	14
hs080	92	8	9	7	49	13

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
hs081	91	38	11	8	56	17
hs083	42	5	8	15	12	16
hs084		6	58	12	46	47
hs085	48	1	9904	127	893	1001
hs086	20	5	16	11	14	15
hs087	107	7	11	18	51	32
hs088	32	19	59	18	67	56
hs089	29	31	85	38	198	61
hs090	35	2	55	28	93	58
hs091	39	337	73	15	216	62
hs092	35	2	56	25	111	58
hs093	4	2	33	10	46	4
hs095		3	2	18	4	24
hs096		3	2	24	4	23
hs097	74	7	36	24	106	19
hs098	255	7	36	21	87	19
hs099	63	9	19	7	61	997
hs100lnp	406	14	33	21	134	32
hs100mod		14	32	27	124	137
hs100	1508	13	23	22	130	63
hs101		34	530	273	5495	1001
hs102	3669	42	238	36	981	1001
hs103		28	177	64	1419	1001
hs104	239	23	29	11	86	80
hs105		9	89	31	115	1001
hs106		17	13	15	504	1001
hs107	317	6	14	12	21	26
hs108	286	36	152	17	165	43
hs109	6020	7	349	44	354	1000
hs110	6	5	11	7	44	5
hs111lnp	52	31	64	16	389	57
hs111	72	31	70	16	389	46
hs112	140	12	35	18	93	47
hs113	2086	6	28	12	147	97
hs114		1	9	73	5	664
hs116		14	22	26	97	1003
hs117	224	6	20	23	158	66
hs118	3	3		12	42	19
hs119	19	7	22	15	30	28
hs21mod	3	2		17	9	3
hs268	6	2		17	37	27
hs35mod	3	2		16	7	3
hs3mod	3	2		6	14	4
hs44new	3	2		14	11	10
hs99exp		12	42	30	213	1001
hubfit	3	2	8	9	12	8
humps	207	1001	257	571	194	1001

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
hypcir	9	8	5	8	8	10
jensmp		11	36	10	56	10
kiwcresc	45	11	17	11	81	23
kowosb	18	18	33	23	40	24
lakes		63	39	20	1045	1001
launch		1	246	673	50	1001
lewispol	6307	1	6		38	22
linspanh	56	2		54		13
loadbal	48	8	58	18	131	62
loghairy	42	1001	249	4173	403	1001
logros	82	50	109	358	148	66
lootsma	9	5	9	16	39	9
lotschd	3	3		15	6	9
lsnnodoc	9	7	8	15	8	11
lsqfit	3	2		8	12	7
madsen	106	25	12	25	72	26
makela1	36	15	8	19	69	19
makela2	54	5	26	8	59	40
makela3	205	25	50	17	238	125
makela4	9	3		8		20
maratosb	8	13	7	33	11	8
maratos	12	10	9	5	21	9
matrix2	26	12	14	21	66	13
maxlika		9	89	31	115	1001
mconcon	100	5	8	10	1	676
mdhole	12	56	70	106	117	68
methanb8		47	306	9	176	221
methanl8	6000	96	499	82	670	640
mexhat	6	10	37	5	19	4
meyer3	36	280	6159	494	776	559
mifflin1	12	23	8	7	36	18
mifflin2	145	10	17	16	124	50
minmaxbd		9	71	78	356	592
minmaxrb	173	3	8	11	112	81
minsurf	9	10	24	21	197	15
mistake	96	18	19	15	160	30
model		2		15		33
mwright	12	12	12	11	38	19
nasty	3	2		2	7	5
nonmsqrt	73	716	7413	83890	1491	167
nuffield_continuum	6	5	9	7	16	15
obstclal	6	2		15	91	7
obstclbl	6	2		13	88	3
obstclbu	6	2		13	75	2
odfits	22	7	17	11	29	49
optcntrl		4	5	134	16	352
optmass		18	2	23	332	1001

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
optprloc		6	12	19	686	438
orthregb	5969	2	9	3	263	64
orthrege	190	180	31	77	858	795
osbornea	17	998	120	152	128	57
osborneb		20	82	25	128	45
oslbqp	3	2		15	12	3
palmer1a		51	205	71	12	102
palmer1b		21	87	26	12	55
palmer1c	3	7		2	62	145
palmer1d	3	6		2	51	34
palmer1e	30	74	186	122	150	353
palmer1	33	33	30	1854	40	28
palmer2a		68	115	392	198	211
palmer2b		16	61	34	8	77
palmer2c	3	5		2	63	298
palmer2e	268	86	191	52	346	133
palmer2		33	44	63	8	34
palmer3a		82	136	199	8	201
palmer3b		21	54	15	17	36
palmer3c	3	5		2	62	206
palmer3e	57	117	293	133	427	1001
palmer3		12	13	553	12	58
palmer4a		52	109	133	8	93
palmer4b		21	52	31	17	64
palmer4c	3	6		2	62	176
palmer4e	175	24	123	38	211	123
palmer4		12	14	1182	12	142
palmer5a	5	1001	1303	12804	321079	1001
palmer5b	5	855	1343	208	3729	961
palmer5c	3	4		2	27	2
palmer5d	3	5		2	26	2
palmer5e	6	3	1313	7933	25502	8
palmer6a	5	137	202	263	271	277
palmer6c	3	6		2	61	159
palmer6e	5	38	198	59	260	47
palmer7a		991	1299	8073	21	1001
palmer7c	3	8		2	65	189
palmer7e	5	1001	1315	12230	925	39
palmer8a	9	50	127	102	104	61
palmer8c	3	7		2	62	152
palmer8e	55	29	92	31	122	86
pentagon	27	12	15	20	23	48
pfit1ls	22	566	480	678	718	453
pfit1	22	566	480	678	718	453
pfit2ls	21	210	175	184	238	217
pfit2	21	210	175	184	238	217
pfit3ls	33	139	289	337	475	272

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
pfit3	33	139	289	337	475	272
pfit4ls	32	126	470	548	755	410
pfit4	32	126	470	548	755	410
polak1	89	8	17	7	86	37
polak2	124	10	225	15	350	321
polak3		24	208	4862	88	234
polak4	33	5	6	10	76	16
polak5	21	45	58	33	68	7
polak6	2592	29	108	301	248	644
portfl1	3	2		10	49	20
portfl2	3	2		9	51	14
portfl3	3	2		11	53	14
portfl4	3	2		10	50	19
portfl6	3	2		9	49	20
powellbs	30	16	15	12	15	106
powellsq	76	4	217	109	52	23
prodp10	21	9	14	16	41	35
prodp11	15	7	10	17	70	27
pspdoc	10	7	15	15	26	10
qudlin	2	2		26	19	2
recipe	11	2	2	3	3	12
res	1	2		10		1
rk23	18015	9	11	12	58	54
robot	286	45	18	10	378	33
rosenbr	44	29	45	45	10	36
rosenmmx	1522	37	41	22	167	226
s365mod		86	31	43	540	91
sim2bqp	3	2		8	10	3
simbqp	3	2		8	11	2
simpllpa	6	2		14		5
simpllpb	6	2		11		4
sineali	12	1001	1351	8025	7334	1001
sineval	51	62	94	110	124	75
sisser	9	19	15	21	18	38
snake		3	6	14	21	1001
spanhyd		11	13	24	61	26
spiral	245	152	107	64	392	96
ssnlbeam	1032	5	36	22	125	39
stancmin	14	2	5	11	6	9
supersim	3	2		2		7
swopf	355	6	24	17	137	290
synthes1	17	5	10	10	22	13
tame	3	2		6	9	2
tointqor	3	2		2	164	8
try-b	18	8	10	20	11	13
twobars	15	8	11	10	32	13
vanderm4	2514	1	57	51	34	36

Problem	filter-al	filterSQP	snopt	ipopt	minos	lancelot
watson	17	21	172	14	118	44
weeds		39	51	32	9	3
womflet	412	9	27	12	135	97
yfit	6	48	95	185	131	103
yfitu		48	95	69	131	103
zangwil2	3	2		2	12	4
zangwil3	3	2		2		3
zecevic2	6	2		9	10	7
zecevic3	19	9	11	22	39	19
zecevic4	15	6	8	10	23	12
zigzag	287	11	23	23	219	43
zy2	9	5	9	10	44	9

The submitted manuscript has been created by UChicago Argonne, LLC, Operator of Argonne National Laboratory (Argonne). Argonne, a U.S. Department of Energy Office of Science laboratory, is operated under Contract No. DE-AC02-06CH11357. The U.S. Government retains for itself, and others acting on its behalf, a paid-up nonexclusive, irrevocable worldwide license in said article to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or on behalf of the Government. The Department of Energy will provide public access to these results of federally sponsored research in accordance with the DOE Public Access Plan. <http://energy.gov/downloads/doe-public-access-plan>.